

ICELOCK® 300 SERIES




- Low build height
- Very light-weight
- Wear-resistant stainless steel pin guide
- Ideal for shower and water prostheses
- Low and moderate impact levels




DIAGRAM

ICELOCK LAYNARD 331-L




For laminated sockets

ICELOCK LAYNARD 331-T



For thermoplastic sockets

ICELOCK LAYNARD 390



For laminated and thermoplastic sockets

PART#	DESCRIPTION	BUILD HEIGHT		WEIGHT	
L-331001	Lanyard 331-L (No Adapter)	12mm	1/2"	22g	0.77oz

PART#	DESCRIPTION	BUILD HEIGHT		WEIGHT	
L-331002	Lanyard 331-T (No Adapter)	14mm	9/16"	42g	1.5oz

PART#	DESCRIPTION	BUILD HEIGHT		WEIGHT	
K-390000	Icelock Lanyard 390	25mm	1"	52g	1.8oz



ICELOCK® 300 SERIES

COMPONENTS FOR L-331001

PART#	DESCRIPTION
L-392012	Cleat with silicone dummy
L-392016	Pull Handle, lanyard
L-392018	Lanyard Cord with connecting screw
L-392110	Bottom Attachment, lamination



COMPONENTS FOR L-331002

PART#	DESCRIPTION
L-392010	Cleat with cover and rivets
L-393012	Cord Cover 40cm, lanyard
L-392016	Pull Handle, lanyard
L-392112	Bottom Attachment, thermoplastic
L-392122	Guide, lanyard
L-393018	Screw 3.5 x 30mm



COMPONENTS FOR K-390000

PART#	DESCRIPTION
K-390001	Spindle Adapter
K-390002	Nut
K-390003	Washer
K-390004	Bottom Attachment
K-390005	Distal Connector
K-390007	Spindle

