

Low Profile Expulsion Valves

One Way Expulsion Valve



CMP19/A

This valve is incredibly low profile, ultra lightweight, and low cost.

- 1mm Build Height
- Less than 1/10 of an Oz.
- Integrated Filter
- Ultra Quiet

Includes: (1) valve

**43/64" or 17mm
Hole Required**

10 Pack: CMP19/B, 30-Pack: CMP19/C

Expulsion Valve Installation

Reduced Shank Drill Bit



CMP20/A

This drill bit can be used to install the KISS® one way expulsion valve, CMP19/A. To ensure proper fit, a 43/64" drill bit OR 17mm drill bit must be used to install the KISS® one way expulsion valve.

- **Size:** 43/64"
- **Reduced Shank**

Includes: (1) Drill Bit

Removable Transtibial Linkage

KISS® WrapStrap-R®

Residue Free, Removable Linkage

- Prevents doffing inversion and donning dislodging
- Stops under sleeve air leakage
- Reliable and strong construction
- Low profile, fully adjustable
- Tapeless and Removable

Includes: (1) KISS® WrapStrap-R®



**CMP24/A
Beige**

10-Pack: CMP24/B



**CMP24/C
Gray**

10-Pack: CMP24/D



**CMP24/E
Black**

10-Pack: CMP24/F



**CMP24/G
Brown**

10-Pack: CMP24/H

Suspension Sleeve Protection

KISS® Soft Edge

Superior Suspension Sleeve protection at the proximal socket edge.

Includes: (1) 60' Strip



**CMP33/A
Beige**



**CMP33/B
Black**