

## 4R57 Rotation adapter

Through incorporation of the rotation adapter above the knee joint, the lower leg may be rotated medially or laterally relative to the socket with the knee flexed.

For the amputee, this mainly translates into enhanced safety. The prosthesis can be swung to the side while driving. This minimises the risk of the prosthetic foot becoming stuck in the area of the pedals. The pedals can be operated using the other leg with no restrictions. In addition, this function allows the amputee to sit in a more comfortable and relaxed position behind the wheel, improving the focus on driving.

Furthermore, the rotation adapter means enhanced comfort for the amputee. It makes everyday activities such as putting on shoes and changing socks easier and allows the amputee to sit comfortably. The sitting position can be varied up to sitting cross-legged. The rotating mechanism is activated through pressing of the release button and is locked automatically.



647G258



There are two available versions which have the same function, but differ in terms of the proximal connection:

- Rotation adapter with pyramid adapter and pyramid receiver: the 4R57 Rotation Adapter is equipped with a proximal pyramid adapter.
- Rotation adapter with threaded connector and pyramid receiver: the 4R57=ST Rotation Adapter is equipped with a proximal thread. This allows for particularly space-saving integration of the adapter which can be screwed into the 4R111=N Lamination Anchor or the 4R43 Lamination Anchor.



≤ 150 kg

<b>Article number</b>	<b>4R57</b>
<b>Material</b>	Stainless steel
<b>Distal connection</b>	Pyramid Receiver
<b>Proximal connection</b>	Pyramid Adapter
<b>System height</b>	22 mm
<b>Weight</b>	170 g
<b>Rotation</b>	max. 360° (without foam cover)
<b>Max. body weight</b>	150 kg

- In order for the 4R57=ST Rotation Adapter to be able to be screwed properly into the lamination anchor, the 4X46=ST Lamination Dummy must be used for laminating. It must be ordered separately (see accessories Page 156).
- The 4R57 cannot be combined with the 2R49, 2R50 or 4R95.

## 2R30 Light metal tube

<b>Article number</b>	<b>2R30</b>
<b>Diameter</b>	30 mm
<b>Max. body weight</b>	up to 100 kg

## 2R36 Light metal tube

<b>Article number</b>	<b>2R36</b>
<b>Diameter</b>	34 mm
<b>for</b>	4R156=* Angled Tube Clamp Adapter
<b>Max. body weight</b>	up to 125 kg

About this  
catalogue

Modular  
lower limb  
protheses

Lower limb  
protheses  
for children

Initial/interim  
protheses

Waterproof  
walking  
devices

Sport  
protheses

Prosthetic  
feet

Adapter

Knee joints

Hip joints

Socket  
Technologies

Cosmetic  
covers

Exoskeletal

Index