



Specifications

Weight Limit	100 kg / 220 lb
Product Weight	783 g / 1.73 lb
Overall Height	18.5 cm / 7.3 in
Distance to Knee Center	3.2 cm / 1.3 in
Flexion	150°
Warranty	2 years

Natural Stance Flexion Knee

- 7° of adjustable stance flexion
- Friction swing phase control
- Shock absorption at heel strike
- Extension assist
- Built-in proximal pyramid and distal tube adapter

Indications: Above knee amputation, low to moderate impact level, K1-K2, maximum weight of 100 kg / 220 lb

Selection

Model No.	Description	Weight Limit
SSK617	Natural Stance Flexion Knee	100 kg / 220 lb



AAASS237
3-Prong Rotatable
Lamination Piece
(page 26)

AAA214-01
Rotatable Female
Insert
(page 26)

SKF200, 300
Kinetic with Pylon
(page 20)

AAA200
Aluminum Pylon
Bonded to Female
Adapter (page 28)



Specifications

Weight Limit	136 kg / 300 lb
Product Weight	630 g / 1.39 lb
Overall Height	13.5 cm / 5.3 in
Distance to Knee Center	3.2 cm / 1.3 in
Flexion	145°
Warranty	2 years

PC Friction Control Knee with Lock

- Polycentric, 4-bar friction control knee with manual lock
- A lightweight, durable knee that can be used in locked position or free motion
- Constant friction braking mechanisms and spring-loaded extension assist helps to create a natural gait
- Built-in proximal pyramid

Indications: Above knee amputation, low to moderate impact level, K1-K2, maximum weight of 136 kg / 300 lb

Selection

Model No.	Description	Weight Limit
SSK602L	PC Friction Control Knee with Lock	136 kg / 300 lb



AAASS237
3-Prong Rotatable
Lamination Piece
(page 26)

AAA214-01
Rotatable Female
Insert
(page 26)

SNF160, 163, 170, 173
Natural
with Pyramid
(page 21)