



Lock Series 150

- no body weight restriction because the lock is not a weight bearing component
- Activity level (walky): 1 to 4 for 15S1 and 15S2
- Activity level (walky): 1 to 3 for 15S3
- mounting height: approx. 23 mm
- suitable for thermoplastic and laminated sockets
- Aluminium housing

The lock series 150 is characterised by its very small design and a high-strength aluminium housing. The aluminium housing can be removed from the deep-drawing socket and used for the laminating socket. Processing is carried out using common deep-drawing or laminating methods. In conjunction with a 12A3, 12A5 or 12A7 Socket Attachment Block, the deviation of the socket gradient and plumb line can be easily corrected.

- Clutch-Lock with „EasyClick“ system: optimised pull-in and release mechanism
- very flat construction
- twist-proof pin guide made of stainless steel
- locking unit completely exchangeable
- with lamination dummy 10S1/E6L (for 15S1), 10S1/E6 (for 15S2 und 15S3)
- incl. special sealing grease 22A100
- please order press button extensions for geriatric patients or big sockets separately

The necessary laminating protection for the locking unit is included in the delivery.

Lock	with Pin	Weight	Item-No.
Clutch-Lock 151	geared	95 g	15S1
Shuttle-Lock 152	rastered	90 g	15S2
Shuttle-Lock 153	plain	85 g	15S3

