



Lock Series 100

- no body weight restriction because the lock is not a weight bearing component
- activity level (walky): 1 to 4 for 10S1 and 10S2
- activity level (walky): 1 to 3 for 10S3
- effective height: approx. 23 mm
- suitable for laminated sockets
- plastic housing is temperature resistant up to 200 °C

The locks of the series 100 distinguish themselves by a very small construction and a shock-resistant plastic housing. Inserted into an AK or BK socket with common lamination techniques, they serve as liner locks. In connection with a socket attachment block 12A3, 12A5 oder 12A7 you can easily correct the deviation of the socket gradient and the plumb line.

- very small construction
- very light
- rotation secured pin guide made of stainless steel
- locking unit is completely exchangeable
- with lamination dummy 10S1/E6L (for 10S1), 10S1/E6 (for 10S2 and 10S3)
- including of sealing grease 22A100
- please order press button extensions for geriatric patients or big sockets separately
- the individual casing varieties can also be ordered separately with the following item numbers: 10S1/E1 for 10S1, 10S2/E1 for 10S2, 10S3/E1 for 10S3

All necessary lamination adapters for the locking unit are included in the delivery.

Lock type	With pin	Weight	Item-No.
Clutch-Lock 101	geared	58 g	10S1
Shuttle-Lock 102	rastered	56 g	10S2
Easy-Lock 103	plain	60 g	10S3

