

TraverseTM

Adaptive hydraulic performance
for every journey.



Fillauer[®]

*“It’s given me back my
sense of adventure.”*

— Josh Contino
Traverse AV User



Traverse AV

Traverse SLX

Traverse K2

One family. Three clear choices.

From K2 users seeking confidence on variable terrain to high-activity K3 users demanding energy return and responsiveness, the **Traverse™** hydraulic family provides a clear pathway to terrain-ready mobility—matching the right foot to every clinical goal.

Confidence on Uneven Ground

Built on a proven hydraulic platform with up to 17° of ankle motion, the Traverse family helps users navigate slopes, uneven terrain, and everyday obstacles with greater stability, comfort, and confidence.

Performance with Simplicity

Waterproof adaptive hydraulic function without batteries, charging requirements, or the complexity of electronic systems for more straightforward fittings and dependable, day-to-day mobility.

Clinician-Driven Customization

Engineered for long-term reliability, responsive performance, and more adjustment range than any hydraulic foot on the market—allowing clinicians to fine-tune heel response, slope handling, and energy return for individualized outcomes.





Traverse K2

Comfortable. Stable. Confidence Building.

Built on the proven SLX hydraulic system, Traverse K2 provides dorsiflexion range, slope handling, and stabilization on a soft, stable K2 foot platform that exceeds traditional K2 feet. Hydraulic dorsiflexion helps with chair rise and standing, while improved toe clearance and rapid foot-flat positioning promote confidence on uneven ground and slopes.



Traverse K2	
Patient Weight	276 lb (125 kg)
Foot Build Height	4.1 in (10.4 cm)
Size	22-30 cm
Product Weight	23.4 oz (662 g)
Range of Motion	12° Plantarflexion / 5° Dorsiflexion
Functional Level	K2
Durable	Meets ISO-22675 Standard
Waterproof	IP67 rating, foot unit is waterproof up to 1 meter
Warranty	24 months
Patient Trial	60 days



Traverse K2

Selection requires foot length and patient weight. Foot shell sold separately.

251-10-XX-XX Traverse K2 foot, foot sizes 22 – 30 cm

Patient Weight		22 cm	23 cm	24 cm	25 cm	26 cm	27 cm	28 cm	29 cm	30 cm
100 – 130 lbs.	45 – 59 kg	22-A1	23-A1	24-A1	25-A1	26-A1				
131 – 161 lbs.	60 – 73 kg	22-B1	23-B1	24-B1	25-B1	26-B1	27-B1	28-B1		
162 – 192 lbs.	74 – 87 kg	22-C1	23-C1	24-C1	25-C1	26-C1	27-C1	28-C1	29-C1	30-C1
193 – 225 lbs.	88 – 102 kg	22-D1	23-D1	24-D1	25-D1	26-D1	27-D1	28-D1	29-D1	30-D1
226 – 260 lbs.	103 – 118 kg	22-E1	23-E1	24-E1	25-E1	26-E1	27-E1	28-E1	29-E1	30-E1
261 – 276 lbs.	119 – 125 kg				25-F2	26-F2	27-F2	28-F2	29-F2	30-F2



Traverse SLX

Smooth. Versatile. Reliable.

A trusted low-profile hydraulic solution for K3 users, the Traverse SLX (formerly Motion Foot SLX) delivers responsive stability and terrain adaptation throughout the gait cycle. Its design promotes early-stance stability, controlled progression through stance, and dependable energy return for confidence on slopes, uneven ground, and everyday activities. For transfemoral users, the dorsiflexion stop enhances knee stabilization when it matters most.



Traverse SLX	
Patient Weight	276 lb (125 kg)
Foot Build Height	4.1 in (10.4 cm)
Size	22-30 cm
Product Weight	22.7 oz (645 g)
Range of Motion	14° Plantarflexion / 3° Dorsiflexion
Functional Level	K3
Durable	Meets ISO-22675 Standard
Waterproof	IP67 rating, foot unit is waterproof up to 1 meter
Warranty	36 months
Patient Trial	60 days

Traverse SLX

Selection requires foot length and patient weight. Foot shell sold separately.

213-10-XX-XX Traverse SLX foot, foot sizes 22 – 30 cm



Patient Weight		22 cm	23 cm	24 cm	25 cm	26 cm	27 cm	28 cm	29 cm	30 cm
100 – 130 lbs.	45 – 59 kg	22-A1	23-A1	24-A1	25-A3	26-A3				
131 – 161 lbs.	60 – 73 kg	22-A1	23-A1	24-A1	25-B3	26-B3	27-C5	28-C5		
162 – 192 lbs.	74 – 87 kg	22-B2	23-B2	24-B2	25-C4	26-C4	27-D5	28-D5	29-E6	30-E6
193 – 225 lbs.	88 – 102 kg	22-B2	23-B2	24-B2	25-D4	26-D4	27-E6	28-E6	29-F7	30-F7
226 – 260 lbs.	103 – 118 kg				25-E4	26-E4	27-F6	28-F6	29-G7	30-G7
261 – 276 lbs.	119 – 125 kg						27-G7	28-G7	29-G7	30-G7



Traverse AV

Adaptive. Responsive. High Performance.

Built for high-activity K3 users, the Traverse AV automatic slope adaptation responds to changing terrain, walking speeds, and footwear in real time while delivering responsive energy return throughout the gait cycle. Its hydraulic locking mechanism enhances stability during early and mid-stance, while active dorsiflexion improves toe clearance during swing phase for confident mobility on slopes, uneven ground, and changing terrain.

Traverse AV	
Patient Weight	276 lb (125 kg)
Foot Build Height	4.1 in (10.4 cm)
Size	22-30 cm
Product Weight	28.5 oz (809 g)
Range of Motion	14° Plantarflexion / 3° Dorsiflexion
Functional Level	K3
Durable	Meets ISO-22675 Standard
Waterproof	IP67 rating, foot unit is waterproof up to 1 meter
Warranty	36 months
Patient Trial	60 days

Traverse AV

Selection requires foot length and patient weight. Foot shell sold separately.

236-10-XX-XX Traverse AV foot, foot sizes 22 – 30 cm

Patient Weight		22 cm	23 cm	24 cm	25 cm	26 cm	27 cm	28 cm	29 cm	30 cm
100 – 130 lbs.	45 – 59 kg	22-A1	23-A1	24-A1	25-A3	26-A3				
131 – 161 lbs.	60 – 73 kg	22-A1	23-A1	24-A1	25-B3	26-B3	27-C5	28-C5		
162 – 192 lbs.	74 – 87 kg	22-B3	23-B3	24-B3	25-C5	26-C5	27-D5	28-D5	29-E7	30-E7
193 – 225 lbs.	88 – 102 kg	22-B3	23-B3	24-B3	25-D5	26-D5	27-E7	28-E7	29-F7	30-F7
226 – 260 lbs.	103 – 118 kg				25-E5	26-E5	27-F7	28-F7	29-G7	30-G7
261 – 276 lbs.	119 – 125 kg						27-G7	28-G7	29-G7	30-G7


AllPro

AllPro XTS		
	K4	Build Height 6.4 (16.2 cm) 8.4 in (21.3 cm)
	K3	
		Patient Weight 276 lb (125 kg)
		Sizes 22 – 30 cm
		Recommended L-Codes* L5987 L5984 PDAC Approved
AllPro DM		
	K4	Build Height 6 in (15.2 cm) 8 in (20.3 cm) 10 in (25.4 cm) 12 in (30.5 cm)
	K3	
		Patient Weight 330 lb (150 kg)
		Sizes 22 – 30 cm
		Recommended L-Codes* L5981 PDAC Approved
AllPro DM Pediatric		
	K4	Build Height 6 in (15.2 cm) 8 in (20.3 cm)
	K3	
		Patient Weight 119 lb (54 kg)
		Sizes 19 – 21 cm
		Recommended L-Codes* L5981
AllPro PM		
	K4	Build Height 4.0 in 10 cm
	K3	
		Patient Weight 330 lb (150 kg)
		Sizes 22 – 30 cm
		Recommended L-Codes* L5980 PDAC Approved

Traverse

Traverse K2		
	K2	Build Height 4.1 in 10.4 cm
		Patient Weight 276 lb (125 kg)
		Sizes 22 – 30 cm
		Recommended L-Codes* L5972 L5968
Traverse SLX		
	K3	Build Height 4.1 in 10.4 cm
		Patient Weight 276 lb (125 kg)
		Sizes 22 – 30 cm
		Recommended L-Codes* L5981 L5968
Traverse AV		
	K3	Build Height 4.1 in 10.4 cm
		Patient Weight 276 lb (125 kg)
		Sizes 22 – 30 cm
		Recommended L-Codes* L5981 L5968

Formula

Formula Ultra™		
	K4	Build Height 3 in 7.6 cm
	K3	
		Patient Weight 330 lb (150 kg)
		Sizes 26 – 31 cm
		Recommended L-Codes* L5980 PDAC Approved
Formula Fit™		
	K4	Build Height 2 in 5.1 cm
	K3	
		Patient Weight 176 lb (80 kg)
		Sizes 24 – 28 cm
		Recommended L-Codes* L5980 L5986
Formula Pediatric™		
	K4	Build Height 1.5 in 3.8 cm
	K3	
		Patient Weight 125 lb (57 kg)
		Sizes 16 – 24 cm
		Recommended L-Codes* L5980 L5986
Formula Pediatric Custom		
	K4	Build Height 1.5 in 3.8 cm
	K3	
		Patient Weight 125 lb (57 kg)
		Sizes 16 – 24 cm
		Recommended L-Codes* L5980 L5986 L5910

Aeris Performance LP

Aeris Performance LP		
	K3	Build Height 5.1 in 13 cm
		Patient Weight 276 lb (125 kg)
		Sizes 22 – 30 cm
		Recommended L-Codes* L5981 L5986

Aeris Performance 2

Aeris Performance 2		
	K4	Build Height 6.5 in 16.5 cm
	K3	
		Patient Weight 330 lb (150 kg)
		Sizes 22 – 30 cm
		Recommended L-Codes* L5981 PDAC Approved

Obsidian

Obsidian Adult Running DM		
	K4	Build Height 10.75 in 27.3 cm
	K3	
		Patient Weight 330 lb 150 kg
		Product Weight 19.4 oz 550 g
		Recommended L-Codes* L5999 PDAC Approved
Obsidian Pediatric Running DM		
	K4	Build Height 6.3 in 160 mm
	K3	
		Patient Weight 124 lb 56 kg
		Product Weight 8.5 oz 240 g
		Recommended L-Codes* L5980 L5999
Obsidian Adult Running PM		
	K4	Build Height 2.0 in 5.1 cm
	K3	
		Patient Weight 330 lb 150 kg
		Product Weight 28 oz 800 g
		Recommended L-Codes* L5999 PDAC Approved
Obsidian Pediatric Running PM		
	K4	Build Height 2 in 5.1 cm
	K3	
		Patient Weight 180 lb 82 kg
		Product Weight 19.4 oz 550 g
		Recommended L-Codes* L5980 L5999
Obsidian Sprint		
	K4	Build Height 3.0 in 7.6 cm
		Patient Weight 275 lb 125 kg
		Product Weight 35 oz 1000 g
		Recommended L-Codes* L5999

Ibex

Ibex XD		
	K4	Build Height 7.2 in 18.4 cm
	K3	
		Patient Weight 440 lb (200 kg)
		Sizes 25 – 30 cm
		Recommended L-Codes* L5980 L5986

Wave Comfort

Wave Comfort 3		
	K3	Build Height 4 in 10 cm
		Patient Weight 330 lb (150 kg)
		Sizes 22 – 30 cm
		Recommended L-Codes* L5981 L5986

*Suggested L-Codes are provided as a reference only. It is the responsibility of the practitioner and/or patient care facility submitting this claim to determine and submit the correct coding within all established rules and guidelines.



Rugged. Renewable. Low profile.



Low Profile Foot Shell

The low-profile foot shell combines a streamlined appearance with a low-bulk design for a comfortable fit across a wide range of footwear. A redesigned heel lock enables easy donning and doffing while maintaining a secure fit throughout daily activities.

Specifications

	Foot Shell
Size	22–30 cm
Product Weight	8.2 oz (233 g)
Primary Materials	BIOVYN™ PVC
Warranty	9 months

Ordering Information

Replace **XX** with foot length (22–30 cm). Foot shell includes black protective sock.

Color	Left	Right
03	45-XX-12-03-3LP	46-XX-12-03-3LP
09	45-XX-12-09-3LP	46-XX-12-09-3LP
13	45-XX-12-13-3LP	46-XX-12-13-3LP
99	45-XX-12-99-3LP	46-XX-12-99-3LP

Protective Socks

Size	Part Number
22–24 cm	636202224
25–27 cm	636202527
28–30 cm	636202830



Fillauer®

Fillauer LLC

2710 Amnicola Highway
Chattanooga, TN 37406
423.624.0946

Fillauer Europe

Kung Hans Väg 2
192 68 Sollentuna, Sweden
+46 8 505 332 00

© 2026 Fillauer LLC
AD393/06-02-22/10-01-26