



Trulife Knees

K1-K2



NEW!

SSK625

Safety Knee

**Ideal for
rehabilitation**

K3-K4



SSK615



SSK615-THR

K1-K2



SSK617



SSK602L

Available Now!

www.trulife.com

SSK625 Safety Knee

SINGLE AXIS KNEE WITH BRAKE, STANCE FLEXION AND MANUAL LOCK

Our Safety Knee is ideal for rehabilitation and is built for K1-K2 ambulators. A traditional mechanical knee with a weight activated adjustable brake, adjustable extension assist, and optional locking cable feature. A compact and light design of only 580 grams allows patients a low maintenance and stable solution.

Indications: Low activity K1-K2 transfemoral amputees (including knee disarticulation and higher)

Features

Mechanical knee joint with dual function:

- Weight activated adjustable brake
- 5° of adjustable stance flexion
- Adjustable extension assist
- Cable actuated locking (optional function)

Specifications

Weight Limit: 136 kg / 300 lb

Amputation Level: Transfemoral (knee disartic and higher)

Overall Height: 121mm /4.76"

Product Weight: 580 g / 20.4 oz

Proximal Connection: Male Pyramid

Distal Connection: 30mm Pylon

Stance Flexion Range: 0-5

Knee Flexion Range: 0-145



In Stock Product!

