

# Varos.

## Right from the start.

*Varos Adjustable Socket* is designed to benefit transfemoral amputees starting in the rehabilitation phase as well as later during treatment with the final prosthesis.

**Varos offers the user noticeable benefits in everyday life.**

- Adjustable by the user to account for volume fluctuations and everyday activities (sitting, driving a car) at any time and any place
- Easy donning and doffing – even when seated
- Low complexity and low product weight

**Varos offers professionals modern treatment and distinguishing features.**

- Fast & easy fitting with a simple process – saves time and effort for patient and CPO
- Can be assembled using basic tools
- Improves the user's perceived safety and stability
- Secure suspension may contribute to better control of prosthesis & movements
- Greater variety of training possibilities



# ottobock.



## Varos.

Flexible, customized  
and lightweight.



The Varos socket and Varos liner are recommended as a combination for reliable interim and definitive fittings for users with a transfemoral amputation. The socket kit allows for quick assembly and custom adaptation. This significantly reduces both the number and duration of visits the patient requires for adjusting the prosthesis.

The special Varos liner evenly distributes pressure on the residual limb. The fabric adhesive strips and the distal magnetic connector result in exceptionally good connection in the socket.

As a result, this offers users the advantages of high flexibility and functionality in comparison with conventional sockets.

### Technical data

#### 5A60 Varos Socket (Example 5A60=R-MC)

Size	S	SC*	M	MC*	L
K Level / Mobility Grade	1 to 4	1 to 4	1 to 4	1 to 4	1 to 4
Maximum body weight	220 lbs (100 kg)	220 lbs (100 kg)	220 lbs (100 kg)	220 lbs (100 kg)	275 lbs (125 kg)
Proximal residual limb circumference (mm)	410–510	460–580	460–580	520–650	520–650
Distal residual limb circumference (mm)	320–390	320–390	350–440	350–440	400–490
Residual limb length (mm)	200–320	200–320	200–320	200–320	200–320

#### 6Y200 Varos Liner (Example 6Y200=M-2)

Size	S-1	SC-1*	S-2	SC-2*	M-1	MC-1*	M-2	MC-2*	L-1	L-2
Proximal residual limb circumference (mm)	420–490	480–550	450–520	510–580	480–550	530–610	510–580	560–650	530–610	560–650
Distal residual limb circumference (mm)	310–350	310–350	330–370	330–370	360–410	360–410	390–440	390–440	400–450	430–490

Please note, it is not possible to combine size L-Large liners with sockets of any other size.

\*-C included in an item number indicates “conical”

[www.ottobock.com](http://www.ottobock.com)

US: P 800 328 4058 | F 800 962 2549

CA: P 800 665 3327 | F 800 463 3659