

COMPONENT		BUILD HEIGHT	WEIGHT	PART NUMBER
1	WATERPROOF TUBE ADAPTER Titanium 250 mm 30 mm diameter	95 mm (min)	255 g (max)	TA WT250 30
el el	WATERPROOF TUBE ADAPTER Titanium 430 mm 30 mm diameter	95 mm (min)	390 g (max)	TA WT430 30
	TUBE CLAMP Titanium 30 mm diameter	51 mm	82 g	TC T 30
	DOUBLE ENDED ADAPTER Titanium 35 mm	35 mm	95 g	DR T35
	DOUBLE ENDED ADAPTER Titanium 45 mm	45 mm	110 g	DR T45
	DOUBLE ENDED ADAPTER Titanium 60 mm	60 mm	123 g	DR T60
	DOUBLE ENDED ADAPTER Titanium 75 mm	75 mm	136 g	DR T75
TO LOVE	4-HOLE PYRAMID RECEIVER Titanium Rotatable	19 mm	90 g	4HPRR T
	4-HOLE PYRAMID ADAPTER w/Pin-Lock Hole, Rotatable Titanium	7 mm	74 g	4HPHR T
	THREADED ADAPTER W/ PIN LOCK HOLE Stainless Steel	3.2 mm	66.4 g	TAH S

COMPONENT		BUILD HEIGHT	WEIGHT	PART NUMBER
	THREADED RECEIVER Stainless Steel	13.2 mm	64.5 g	TR S
e of o	LOW-PROFILE THREADED CONNECTOR, Titanium	14.5 mm	33 g	LPTC T
q q	4-HOLE PLATE, ROUND, THREADED, TIE GROOVE, Aluminum	9.7 mm	59 g	4HLP RTG A
	3-PRONG ANCHOR, ROTATABLE, Stainless Steel	8 mm	124 g	3PA R
	3 PRONG ANCHOR W/ RECEIVER, ROTATABLE Stainless Steel	11.2 mm	190 g	3PA AHR S
-	3 PRONG ANCHOR, ADAPTER W/ PIN LOCK HOLE, ROTATABLE Stainless Steel	21.2 mm	188 g	3PA RR S
V	4-PRONG ANCHOR, ROTATABLE Stainless Steel	8 mm	158 g	4PA R
	4 PRONG ANCHOR W/ RECEIVER, ROTATABLE Stainless Steel	11.1 mm	224 g	4PA AHR S
W	4 PRONG ANCHOR, ADAPTER W/ PIN LOCK HOLE, ROTATABLE Stainless Steel	21.2 mm	223 g	4PA RR S

NOTE: Please refer to the instructions (IFU) for each product's specific water limitations and appropriate maintenance processes.





WATERPROOF K2 LEG

Whether your patient is surfing in the ocean, working in high humidity, or dancing in the rain, College Park offers accommodating innovation. Check out this example of a fully waterproof leg solution!









4-PRONG ANCHOR





Aura features







WATERPROOF



















INTELLIWEAVE COMPOSITE

INTEGRATED PYRAMID

WATERPROOF

