

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2015/830**

570  
Version 3.0

Primer for PUR - green label  
Revision date 27-Jan-2021

Print date 03-Feb-2021

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

570 Primer for PUR - green label

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

**Relevant identified uses**

Primers

**1.3 Details of the supplier of the safety data sheet**

**Supplier**

Renia Gesellschaft mbH  
Ostmerheimer Straße 516 Telephone: +492216307990  
51109 Köln E-mail: info@renia.com  
Deutschland Website: www.renia.com

**Department responsible for information**

E-mail (competent person) labor@renia.com

**1.4 Emergency telephone number**

Emergency telephone number Grimme: +49-221-630799-17  
Only available during office hours.

**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

- \* Flam. Liq. 2; flammable liquids; H225 Highly flammable liquid and vapour.
- \* Eye Irrit. 2; Serious eye damage/eye irritation; H319 Causes serious eye irritation.
- \* STOT SE 3 Narcotic effects; STOT-single exposure; H336 May cause drowsiness or dizziness.
- \* Skin Sens. 1; Skin sensitisation; H317 May cause an allergic skin reaction.

**2.2 Label elements**

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Hazard pictograms**



**Signal word**

Danger

**Hazard statements**

H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H317 May cause an allergic skin reaction.

**Precautionary Statements**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing vapours.  
\* P280 Wear protective gloves and eye/face protection.  
P337 + P313 If eye irritation persists: Get medical advice/attention.  
P370 + P378 In case of fire: Use extinguishing powder or sand to extinguish.  
P403 + P235 Store in a well-ventilated place. Keep cool.

**Hazard components for labelling**

aromatic polyisocyanate  
Ethyl acetate  
m-tolylidene diisocyanate, oligomerisation product

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2015/830**

570  
Version 3.0

Primer for PUR - green label  
Revision date 27-Jan-2021

Print date 03-Feb-2021

\* m-tolylidene diisocyanate

**Supplemental hazard information**

EUH066 Repeated exposure may cause skin dryness or cracking.

**2.3 Other hazards**

No information available.

**SECTION 3: Composition / information on ingredients**

**3.2 Mixtures**

**Description**

Aromatic polyisocyanate in ethyl acetate.

**Hazardous ingredients**

| CAS No.<br>EC No.<br>INDEX No.            | Substance name<br>REACH No.<br>Classification according to Regulation (EC) No 1272/2008 [CLP]                                                                                                                                                                                              | weight-%    |
|-------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|
| 141-78-6<br>205-500-4<br>607-022-00-5     | <b>Ethyl acetate</b><br>01-2119475103-46<br>Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336 / EUH066                                                                                                                                                                                | 90,0 < 95,0 |
| 9017-01-0<br>-<br>-                       | <b>m-tolylidene diisocyanate, oligomerisation product</b><br>01-2119950331-47-0000<br>Skin Sens. 1B H317                                                                                                                                                                                   | 6,0 < 7,0   |
| 26006-20-2<br>-<br>-                      | <b>aromatic polyisocyanate</b><br>Skin Sens. 1 H317 / Eye Irrit. 2 H319                                                                                                                                                                                                                    | 2,0 < 3,0   |
| * 26471-62-5<br>247-722-4<br>615-006-00-4 | <b>m-tolylidene diisocyanate</b><br>01-2119454791-34<br>Skin Irrit. 2 H315 / Skin Sens. 1 H317 / Eye Irrit. 2 H319 / Acute Tox. 2 H330 / Resp. Sens. 1 H334 / STOT SE 3 H335 / Carc. 2 H351 / Aquatic Chronic 3 H412<br>Specific concentration limit (SCL):<br>Resp. Sens. 1 H334: >= 0,10 | 0 < 0,1     |

**Remark**

Full text of H- and EUH-statements: see section 16.

**SECTION 4: First aid measures**

**4.1 Description of first aid measures**

**General information**

Remove affected person from the danger area and lay down.

**Following inhalation**

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. No mouth-to-mouth or mouth-to-nose resuscitation. Use Ambu bag or ventilator. Medical treatment necessary.

**Following skin contact**

After contact with skin, wash immediately with plenty of water and soap. Take off contaminated clothing and wash it before reuse. In case of skin reactions, consult a physician. Rub greasy ointment into the skin.

**After eye contact**

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

**After ingestion**

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Do NOT induce vomiting.

**Self-protection of the first aider**

First aider: Pay attention to self-protection!

**4.2 Most important symptoms and effects, both acute and delayed**

**Symptoms**

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2015/830**

570  
Version 3.0

Primer for PUR - green label  
Revision date 27-Jan-2021

Print date 03-Feb-2021

dizziness. Nausea. headache. Unconsciousness.

**4.3 Indication of any immediate medical attention and special treatment needed**

Treat symptomatically. Transport affected person in lying position, in case of shortness of breath in half-sitting position. Where appropriate artificial ventilation. Subsequent observance for pneumonia and lung oedema.

**SECTION 5: Firefighting measures**

**5.1 Extinguishing media**

**Suitable extinguishing media**

Carbon dioxide (CO<sub>2</sub>), alcohol resistant foam, Extinguishing powder, ABC-powder, spray mist, (water), Dry sand.

**Unsuitable extinguishing media**

Full water jet. Strong water jet.

**5.2 Special hazards arising from the substance or mixture**

Flammable. Vapours can form explosive mixtures with air. Do not inhale explosion and combustion gases.

**5.3 Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

**5.4 Additional information**

Suppress gases/vapours/mists with water spray jet. Use water spray jet to protect personnel and to cool endangered containers. Remove product from area of fire. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

**SECTION 6: Accidental release measures**

**6.1 Personal precautions, protective equipment and emergency procedures**

Avoid contact with eyes and skin. Use personal protection equipment. Remove all sources of ignition. Provide adequate ventilation. The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration. Do not breathe gas/fumes/vapour/spray.

**6.2 Environmental precautions**

Do not allow to enter into surface water or drains. Cover drains.

**6.3 Methods and material for containment and cleaning up**

- \* Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

**6.4 Reference to other sections**

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

**SECTION 7: Handling and storage**

**7.1 Precautions for safe handling**

**Advices on safe handling**

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe). If handled uncovered, arrangements with local exhaust ventilation should be used if possible. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

**Advices on general occupational hygiene**

When using do not eat, drink, smoke, sniff. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. Before starting work, apply solvent-resistant skincare preparations.

**Further information**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Vapours/aerosols must be exhausted directly at the point of origin. Take precautionary measures against static discharge.

**7.2 Conditions for safe storage, including any incompatibilities**

**Requirements for storage rooms and vessels**

Keep only in the original container in a cool, well-ventilated place. Keep container tightly closed. Store in a well-ventilated and dry room at temperatures between 10 °C and 30 °C. Ensure adequate ventilation of the storage area.

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2015/830**

570  
Version 3.0

Primer for PUR - green label  
Revision date 27-Jan-2021

Print date 03-Feb-2021

**Hints on joint storage**

Do not store together with: Oxidizing agent, Pyrophoric or self-heating substances. Store packaging and ignitable materials separately. Keep away from food, drink and animal feedingstuffs.

**Further information on storage conditions**

Floors should be impervious, resistant to liquids and easy to clean. Store small packages in a suitable, robust cabinet.

**7.3 Specific end use(s)**

Solvents/Thinner.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

**Occupational exposure limit values**

| CAS No.    | Substance name | Source | Long-term /short-term (Spitzenbegrenzung) |
|------------|----------------|--------|-------------------------------------------|
| * 141-78-6 | Ethyl acetate  | WEL    | 734 / 1.468 ( - ) mg/m <sup>3</sup>       |

**Additional information**

Long-term: long-term occupational exposure limit value

short-term: short-term occupational exposure limit value

**Biological limit values**

No data available

**DNEL worker**

| CAS No.      | Substance name                                     | DNEL type                            | DNEL value              |
|--------------|----------------------------------------------------|--------------------------------------|-------------------------|
| 141-78-6     | Ethyl acetate                                      | DNEL long-term inhalative (systemic) | 1,468 mg/l              |
| 141-78-6     | Ethyl acetate                                      | DNEL acute inhalative (local)        | 1,468 mg/l              |
| 141-78-6     | Ethyl acetate                                      | DNEL long-term dermal (systemic)     | 63 mg/kg                |
| * 26471-62-5 | m-tolylidene diisocyanate                          | DNEL long-term inhalative (systemic) | 0,035 mg/m <sup>3</sup> |
| * 26471-62-5 | m-tolylidene diisocyanate                          | DNEL acute inhalative (systemic)     | 0,14 mg/m <sup>3</sup>  |
| * 26471-62-5 | m-tolylidene diisocyanate                          | DNEL acute inhalative (local)        | 0,14 mg/m <sup>3</sup>  |
| * 26471-62-5 | m-tolylidene diisocyanate                          | DNEL long-term inhalative (local)    | 0,035 mg/m <sup>3</sup> |
| 9017-01-0    | m-tolylidene diisocyanate, oligomerisation product | DNEL long-term inhalative (local)    | 0,345 mg/m <sup>3</sup> |

**DNEL Consumer**

| CAS No.  | Substance name | DNEL type                            | DNEL value |
|----------|----------------|--------------------------------------|------------|
| 141-78-6 | Ethyl acetate  | DNEL acute inhalative (systemic)     | 0,734 mg/l |
| 141-78-6 | Ethyl acetate  | DNEL long-term inhalative (local)    | 0,734 mg/l |
| 141-78-6 | Ethyl acetate  | DNEL long-term dermal (systemic)     | 37 mg/kg   |
| 141-78-6 | Ethyl acetate  | DNEL long-term inhalative (systemic) | 0,037 mg/l |
| 141-78-6 | Ethyl acetate  | DNEL long-term oral (repeated)       | 4,5 mg/kg  |
| 141-78-6 | Ethyl acetate  | DNEL acute inhalative (local)        | 0,367 mg/l |

**PNEC**

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2015/830**

570  
Version 3.0

Primer for PUR - green label  
Revision date 27-Jan-2021

Print date 03-Feb-2021

| CAS No.      | Substance name                                     | PNEC type                         | PNEC Value     |
|--------------|----------------------------------------------------|-----------------------------------|----------------|
| 141-78-6     | Ethyl acetate                                      | PNEC aquatic, freshwater          | 0,26 mg/l      |
| 141-78-6     | Ethyl acetate                                      | PNEC aquatic, marine water        | 0,026 mg/l     |
| 141-78-6     | Ethyl acetate                                      | PNEC sediment, freshwater         | 0,34 mg/kg     |
| 141-78-6     | Ethyl acetate                                      | PNEC sediment, marine water       | 0,034 mg/kg    |
| 141-78-6     | Ethyl acetate                                      | PNEC soil, freshwater             | 0,22 mg/kg     |
| * 26471-62-5 | m-tolylidene diisocyanate                          | PNEC aquatic, freshwater          | 0,013 mg/l     |
| * 26471-62-5 | m-tolylidene diisocyanate                          | PNEC aquatic, marine water        | 0,001 mg/l     |
| * 26471-62-5 | m-tolylidene diisocyanate                          | PNEC sewage treatment plant (STP) | 1 mg/l         |
| * 26471-62-5 | m-tolylidene diisocyanate                          | PNEC soil, freshwater             | 1 mg/kg dw     |
| 9017-01-0    | m-tolylidene diisocyanate, oligomerisation product | PNEC aquatic, freshwater          | 0,1 mg/l       |
| 9017-01-0    | m-tolylidene diisocyanate, oligomerisation product | PNEC sediment, freshwater         | 3.302 mg/kg dw |
| 9017-01-0    | m-tolylidene diisocyanate, oligomerisation product | PNEC aquatic, marine water        | 0,01 mg/l      |
| 9017-01-0    | m-tolylidene diisocyanate, oligomerisation product | PNEC sediment, marine water       | 330 mg/kg dw   |
| 9017-01-0    | m-tolylidene diisocyanate, oligomerisation product | PNEC sewage treatment plant (STP) | 0,1 mg/l       |
| 9017-01-0    | m-tolylidene diisocyanate, oligomerisation product | PNEC soil, freshwater             | 658 mg/kg dw   |

## 8.2 Exposure controls

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

### Personal protection equipment

#### **Respiratory protection**

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Combination filtering device (EN 14387). Use the following filter types for cleaning waste gases:

#### **Hand protection**

Suitable material: NBR (Nitrile rubber)

Thickness of the glove material:  $\geq 0,4$  mm

\* Breakthrough time (maximum wearing time):  $\geq 480$  min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### **Eye/face protection**

Wear closely fitting protective glasses in case of splashes.

#### **Body protection**

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn.

Wear anti-static footwear and clothing

### Environmental exposure controls

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### **Appearance**

Physical state

liquid

Colour

transparent

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2015/830**

570  
Version 3.0

Primer for PUR - green label  
Revision date 27-Jan-2021

Print date 03-Feb-2021

**Safety characteristics**

|                                         |                |
|-----------------------------------------|----------------|
| Odour                                   | characteristic |
| Odour threshold                         | not determined |
| * pH at 20 °C:                          | not determined |
| Melting point/freezing point            | not determined |
| Initial boiling point and boiling range | 77 °C          |
| Flash point                             | -4 °C          |
| Evaporation rate at 20°C                | not determined |
| Burning time (s)                        | not applicable |
| Lower explosion limit at 20°C           | 2,1 Vol-%      |
| Upper explosion limit at 20°C           | 11,5 Vol-%     |
| Vapour pressure at 20°C                 | 97 mbar        |
| Density at 20°C                         | 0,887 kg/l     |
| Water solubility (g/L) at 20°C          | not determined |
| Partition coefficient: n-octanol/water  | see section 12 |
| Ignition temperature in °C              | 460 °C         |
| Decomposition temperature               | not determined |
| Viscosity                               | 6,46 mPas      |
| Explosive properties                    | not relevant   |
| Oxidising properties                    | not relevant   |

**9.2 Other information**

not applicable

**SECTION 10: Stability and reactivity**

**10.1 Reactivity**

No hazardous reaction when handled and stored according to provisions.

**10.2 Chemical stability**

The study does not need to be conducted because the substance is known to be stable at room temperature for prolonged periods of time (days).

**10.3 Possibility of hazardous reactions**

Gases / vapours, highly flammable. Vapours can form explosive mixtures with air.

**10.4 Conditions to avoid**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**10.5 Incompatible materials**

Acid, concentrated, Oxidising agent, strong.

**10.6 Hazardous decomposition products**

Thermal decomposition can lead to the escape of irritating gases and vapours.

**SECTION 11: Toxicological information**

**11.1 Information on toxicological effects**

**Acute toxicity**

Based on available data, the classification criteria are not met.

**Ethyl acetate**

LD50: oral (Rat): > 5.620 mg/kg

LD50: dermal (Rabbit): > 18.000 mg/kg

LC50: inhalative (Rat): = 56 mg/l (4 h)

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2015/830**

570  
Version 3.0

Primer for PUR - green label  
Revision date 27-Jan-2021

Print date 03-Feb-2021

**aromatic polyisocyanate**

LD50: oral (Rat): > 5.000 mg/kg

LD50: dermal (Rat): > 1 mg/kg

LC50: inhalative (Rat): > 3.003 mg/l (4 h)

**m-tolylidene diisocyanate, oligomerisation product**

LD50: oral (Rat): > 2.000 mg/kg; (OECD 423)

LC50: inhalative (Rat): > 1.839 mg/l (4 h); (OECD 403)

\* **m-tolylidene diisocyanate**

LD50: oral (Rat): > 2.000 mg/kg; (OECD 401)

\* LC50: inhalative (Rat): = 0,48 mg/l (4 h); (OECD 403)

\* LD50: dermal (Rabbit): > 9.400 Mg/kg KG; (OECD 402)

**Skin corrosion/irritation**

Based on available data, the classification criteria are not met.

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Respiratory or skin sensitisation**

May cause an allergic skin reaction.

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Practical experience/human evidence**

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: Headache, Dizziness, fatigue, amyosthenia, Drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

**SECTION 12: Ecological information**

**12.1 Toxicity**

Based on available data, the classification criteria are not met.

***Acute (short-term) fish toxicity***

**Ethyl acetate**

LC50: (Oncorhynchus mykiss (Rainbow trout)): = 230 mg/l (96 h)

**m-tolylidene diisocyanate, oligomerisation product**

LC50: (Brachydanio rerio (zebra-fish)): > 100 mg/l (96 h)

Method: OECD 203

**m-tolylidene diisocyanate**

\* LC50: (Oncorhynchus mykiss (Rainbow trout)): = 133 mg/l (96 h)

Method: OECD 203

***Acute (short-term) toxicity to aquatic algae and cyanobacteria***

**Ethyl acetate**

LC50: (Desmodesmus subspicatus): = 5.600 mg/l (48 h)

**m-tolylidene diisocyanate, oligomerisation product**

ErC50: (Desmodesmus subspicatus): > 100 mg/l (72 h)

Method: OECD 201



**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2015/830**

570  
Version 3.0

Primer for PUR - green label  
Revision date 27-Jan-2021

Print date 03-Feb-2021

- m-tolylidene diisocyanate**  
\* ErC50: (Skeletonema costatum): = 3.230 mg/l (96 h)  
Method: OECD 201
- Acute (short-term) toxicity to crustacea**  
**Ethyl acetate**  
EC50 (Daphnia magna (Big water flea)): = 165 mg/l (48 h)
- m-tolylidene diisocyanate, oligomerisation product**  
EC50 (Daphnia magna (Big water flea)): > 100 mg/l (48 h)  
Method: OECD 202
- m-tolylidene diisocyanate**  
\* EC50 (Daphnia magna (Big water flea)): = 12,5 mg/l (48 h)  
Method: OECD 202

## 12.2 Persistence and degradability

**m-tolylidene diisocyanate, oligomerisation product**  
Biodegradation; (Activated sludge); Biochemical oxygen demand (BOD) = 4 % (28 d )  
Method: OECD 301F/ ISO 9408/ EEC 92/69/V, C.4-D  
Not readily biodegradable (according to OECD criteria)

## 12.3 Bioaccumulative potential

- \* Partition coefficient: n-octanol/water = 0,68

## 12.4 Mobility in soil

No information available.

## 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6 Other adverse effects

No information available.

# SECTION 13: Disposal considerations

## 13.1 Waste treatment methods

### Product/Packaging disposal

Do not empty into drains; dispose of this material and its container in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

### Waste codes/waste designations according to EWC/AVV

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

### Other disposal recommendations

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

# SECTION 14: Transport information

## 14.1 UN number

UN 1993

## 14.2 UN proper shipping name

### Land transport (ADR/RID)

ENTZÜNDBARER FLÜSSIGER STOFF, N.A.G. (enthält Ethylacetat)

### Sea transport (IMDG)

Flammable liquid, n.o.s. (contain Ethyl acetate)

### Air transport (ICAO-TI / IATA-DGR)

Flammable liquid, n.o.s. (contain Ethyl acetate)

## 14.3 Transport hazard class(es)

|                                    |   |
|------------------------------------|---|
| Land transport (ADR/RID)           | 3 |
| Sea transport (IMDG)               | 3 |
| Air transport (ICAO-TI / IATA-DGR) | 3 |



**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2015/830**

570  
Version 3.0

Primer for PUR - green label  
Revision date 27-Jan-2021

Print date 03-Feb-2021

**14.4 Packing group**

|                                    |    |
|------------------------------------|----|
| Land transport (ADR/RID)           | II |
| Sea transport (IMDG)               | II |
| Air transport (ICAO-TI / IATA-DGR) | II |

**14.5 Environmental hazards**

|                          |                |
|--------------------------|----------------|
| Land transport (ADR/RID) | not applicable |
| Sea transport (IMDG)     | not applicable |

**14.6 Special precautions for user**

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage. Advices on safe handling: see parts 6 - 8

**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

No transport as bulk according to IBC Code.

**14.8 Additional information**

**Land transport (ADR/RID)**

tunnel restriction code: D/E

**Sea transport (IMDG)**

\* EmS-Code: F-E, S-E

**Air transport (ICAO-TI / IATA-DGR)**

\* not applicable

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU legislation**

**Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

**Directive 2010/75/EU on industrial emissions**

\* VOC-value (in g/L): 808,944 g/l

**Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]**

**Hazard categories / Named dangerous substances**

P5c Flammable liquids

Quantity 1: 5.000t; Quantity 2: 50.000t

**National regulations**

**15.2 Chemical Safety Assessment**

For the following substances of this mixture a chemical safety assessment has been carried out:

**REACH No.**

**Substance name**

01-2119475103-46

Ethyl acetate

\* 01-2119454791-34

m-tolylidene diisocyanate

01-2119950331-47-0000

m-tolylidene diisocyanate, oligomerisation product

**SECTION 16: Other information**

Relevant R-, H- and EUH-phrases (Number and full text)

|        |                                                                            |
|--------|----------------------------------------------------------------------------|
| H225   | Highly flammable liquid and vapour.                                        |
| * H315 | Causes skin irritation.                                                    |
| H317   | May cause an allergic skin reaction.                                       |
| H319   | Causes serious eye irritation.                                             |
| * H330 | Fatal if inhaled.                                                          |
| * H334 | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| * H335 | May cause respiratory irritation.                                          |
| H336   | May cause drowsiness or dizziness.                                         |

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2015/830**

|             |                              |                        |
|-------------|------------------------------|------------------------|
| 570         | Primer for PUR - green label |                        |
| Version 3.0 | Revision date 27-Jan-2021    | Print date 03-Feb-2021 |

---

- \* H351 Suspected of causing cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
- \* H412 Harmful to aquatic life with long lasting effects.

**Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]**

|                            |                        |
|----------------------------|------------------------|
| Flam. Liq. 2               | On basis of test data. |
| Eye Irrit. 2               | Calculation method.    |
| STOT SE 3 Narcotic effects | Calculation method.    |
| Skin Sens. 1               | Calculation method.    |

**Abbreviations and acronyms**

For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>

**Indication of changes**

- \* Data changed compared with the previous version