

3 & 4 PRONG

Stainless 3 Prong

COMPONENT	PART NUMBER	DESCRIPTION	WEIGHT	BUILD HEIGHT	WEIGHT RATING
	700LAM-TOOL	Laminating Thread Tooling	-	-	-
	SS-300LM	3 Prong Adapter, Male Threads	133 g	3 mm	300 lbs (136 kg)
	SS-700LM	3 Prong with Rotating Stainless Pyramid	258 g	22 mm	300 lbs (136 kg)
	SS-750LM	3 Prong with Rotating Stainless Receiver	258 g	27 mm	300 lbs (136 kg)
	SS-800BASE	3 Prong Adapter	119 g	7 mm	300 lbs (136 kg)
	SS-800LM	3 Prong with Rotating Stainless Pyramid	208 g	13 mm	300 lbs (136 kg)
	SS-810LM	3 Prong with Fixed Pyramid	130 g	9 mm	276 lbs (125 kg)
	SS-850LM	3 Prong with Rotating Stainless Receiver	209 g	20 mm	300 lbs (136 kg)

3 & 4 PRONG

Stainless 4 Prong

COMPONENT	PART NUMBER	DESCRIPTION	WEIGHT	BUILD HEIGHT	WEIGHT RATING
	SS-740L	4 Prong with Pyramid	128 g	7 mm	300 lbs (136 kg)
	SS-840BASE	4 Prong Adapter	99 g	10 mm	276 lbs (125 kg)
	SS-840LM	4 Prong with Rotating Stainless Pyramid	181 g	16 mm	276 lbs (125 kg)
	SS-845LM	4 Prong with Rotating Stainless Receiver	184 g	23 mm	276 lbs (125 kg)

Stainless 3 Prong with Titanium

	TI-700LM	3 Prong with Rotating Titanium Pyramid	198 g	22 mm	300 lbs (136 kg)
	TI-750LM	3 Prong with Rotating Titanium Receiver	213 g	27 mm	300 lbs (136 kg)
	TI-800LM	3 Prong with Rotating Titanium Pyramid	147 g	9 mm	276 lbs (125 kg)
	TI-850LM	3 Prong with Rotating Titanium Receiver	156 g	15 mm	276 lbs (125 kg)

3 & 4 PRONG

Stainless 4 Prong with Titanium

COMPONENT	PART NUMBER	DESCRIPTION	WEIGHT	BUILD HEIGHT	WEIGHT RATING
	TI-840LM	4 Prong with Rotating Titanium Pyramid	145 g	16 mm	276 lbs (125 kg)
	TI-845LM	4 Prong with Rotating Titanium Receiver	150 g	23 mm	276 lbs (125 kg)

Titanium 4 Prong

	TI-740B	4 Prong Adapter, Male Threads	57 g	5 mm	365 Lbs (166 Kg)
	TI-740L	4 Prong with Pyramid	68 g	7 mm	365 Lbs (166 Kg)
	TI-740L-S	4 Prong with Pyramid, SLOTS	79 g	7 mm	365 Lbs (166 Kg)
	TI-740-RM	4 Prong with Rotating Titanium Pyramid	130 g	23 mm	365 Lbs (166 Kg)
	TI-745-RF	4 Prong with Rotating Titanium Receiver	136 g	28 mm	365 Lbs (166 Kg)