

JMS 500

The JMS 500 High Density Polyethylene Plastic Sheets are offered a variety of colors, such as white, black, blue, red, multicolor, and fleshtone. There are a variety of thicknesses available as well, from 1.0mm to 5.0mm.



HIGH MOLECULAR WEIGHT, HIGH DENSITY POLYETHYLENE PLASTIC SHEETS

WHITE	BLACK	BLUE	RED	PICASSO*	THICKNESS	SHEET SIZE	SF/SHEET
50010W-1	–	–	–	–	1.0 mm	36" x 37.50"	9.375
50012W-1	50012K-1	50012B-1	50012R-1	50012P-1	2.0 mm	36" x 37.50"	9.375
50013W-1	50013K-1	50013B-1	50013R-1	50013P-1	3.0 mm	36" x 37.50"	9.375
50014W-1	50014K-1	50014B-1	50014R-1	50014P-1	4.0 mm	36" x 37.50"	9.375
50015W-1	50015K-1	50015B-1	50015R-1	50015P-1	5.0 mm	36" x 37.50"	9.375

* Picasso is a swirl consisting of blue, yellow, red and green.

FLESHSTONE	THICKNESS	SHEET SIZE	SF/SHEET
50001F-1	1.0 mm	36" x 37.50"	9.375
50002F-1	2.0 mm	36" x 37.50"	9.375
50003F-1	3.0 mm	36" x 37.50"	9.375
50004F-1	4.0 mm	36" x 37.50"	9.375
50005F-1	5.0 mm	36" x 37.50"	9.375

Processing Information:

JMS 500 should be formed at temperatures of 325 – 375 deg. F for between 4 – 12 minutes, depending on thickness and individual oven conditions. Shrinkage is normal when heated.

Thickness tolerances:

1.0 mm to 1.5 mm: ± 0.2 mm

2.0 mm to 4.0 mm: ± 0.3 mm

5.0 mm to 6.0 mm: ± 0.5 mm

Pairs per sheet: 4"x8"= 18-20 pairs, 5"x9"=13-14 pairs.