

R16 Renegade LP-AT

Product features

- The most dynamic, versatile, and durable Renegade prosthetic foot
- EnduraCore® Technology delivers 3 times the fatigue life of standard laminates
- Split-toe design delivers +/- 15° degrees of inversion/eversion for enhanced stability
- Z-Shock-Technology™ absorbs shear forces providing greater user comfort
- Lightweight construction



Technical data

K-Level	3, 4
Max. body weight	365 lbs / 166 kg
Sizes	22-31 cm
Heel height	3/8" / 10 mm
Weight with footshell*	26.81 oz / 760 g
Build height*	5 1/2" / 140 mm

* Reference size is 26 cm.

R16 Renegade LP-AT

Order form

Customer		Shipping address (if different from customer address)	
Customer no.		Customer no.	
Company		Company	
Street		Street	
Postal code/city		Postal code/city	
O&P professional		Customer ref.	

Stiffness chart

Body weight	Activity level		
	Low	Moderate	High
100–115 lbs / 44–52 kg	1	1	2
116–130 lbs / 53–59 kg	1	2	3
131–150 lbs / 60–68 kg	2	3	4
151–170 lbs / 69–77 kg	3	4	5
171–195 lbs / 78–88 kg	4	5	6
196–220 lbs / 89–100 kg	5	6	7
221–255 lbs / 101–116 kg	6	7	8
256–285 lbs / 117–130 kg	7	8	9
286–325 lbs / 131–147 kg	8	9	–
326–365 lbs / 148–166 kg	9	–	–

Foot module part number

Reference number	Stiffness	Size
R16 - 00 - 0 - RU		
	Stiffness	Size (cm)
	1 – 9	22, 23, ..., 31

Footshell part number

Reference number	Generation	Profile	Cap	Size	Color	Side
FTC	-	-			4 - R	
	↓	↓	↓	↓	↓	↓
	Generation	Profile	Cap	Size (cm)	Color	Side
	2-3	M Mid	0 Yes	22, 23, ..., 31	L Light	L Left
		H High	1 No		M Medium	R Right
					D Dark	

Scope of delivery

- R16* Renegade LP-AT
- KIT-00-11* Set of heel wedges
- S0-NPS-200* Spectra protective sock black
- RS6-SP-0* Sole plate

Accessories & spare parts

- S0-NPS-100* Spectra protective sock white
- ACC-00-10300-00 Footshell removal tool

Available footshell variants

- FTC-3M-0*: Footshell standard (with cap)
- FTC-3M-1*: Footshell standard (without cap)
- FTC-2H-1*: Footshell high profile (without cap)