

4-Hole Connector without Pyramid Hole

The non-rotatable 4-hole titanium connector without pyramid hole attaches to any socket or knee with a distal 4-hole pattern. It comes with 4 flat head screws. It provides more strength than the 1217T. Titanium is forged and machined for a high strength and quality. This product has a 2 year warranty.

P/N	Material	Product Weight	Weight Limit
1227T	Titanium	73g	159kg



4-Hole Connector, Pyramid

1 Titanium 4-Hole Connector, Pyramid

The non-rotatable 4-hole titanium pyramid adapter attaches to any socket or knee with a distal 4-hole pattern. 4 flat head screws are provided with every pyramid. The 1217T is manufactured by a forged and machined combination providing for a high quality, light weight and strong product. This product has a 2 year warranty.

② Stainless Steel 4-Hole Connector, Pyramid

The non-rotatable 4-hole stainless steel pyramid adapter attaches to any socket or knee with a 4-hole pattern. 4 flat head screws are provided with every pyramid. The 1217S is manufactured from high strength stainless steel alloy providing for a high quality and strong product. This product has a 2 year warranty.

3 Aluminium 4-Hole Connector, Pyramid

The non-rotatable 4-hole aluminium pyramid adapter attaches to any socket or knee with a 4-hole pattern. 4 flat head screws are provided with every pyramid. The 1217A is manufactured by a forged and machined combination providing for a high quality and strong product. This product has a 2 year warranty.

P/N	Material	Product Weight	Weight Limit
①1217T	Titanium	70g	136kg
②1217S	Stainless Steel	111g	125kg
③1217A	Aluminium	81g	114kg



4-Hole Connector, Receiver The 4-hole connector receiver is used to connect to

The 4-hole connector receiver is used to connect to any 4-hole thread system and pyramid connection. Used 4 flat head screws to connect to 4-hole connector. 4 set screws are used for anchoring the making pyramid system as well as for making angular adjustment for alignment. Apply recommended torque to alignment adjustment screws for connection. Apply loctite to all screws once the alignment and connection is finalized. This product has a 2 year warranty.

P/N	Material	Product Weight	Weight Limit
①1218T	Titanium	53g	136kg
②1218S	Stainless Steel	160g	125kg
③1218A	Aluminium	84g	114kg

www.stngco.com