



Rotatable Socket Adapter with Pyramid Receiver I

The 4-hole connector receiver is used to connect to any 4-hole thread system and pyramid connection. This adapter can be rotated. Used 4 flat head screws to connect to 4-hole connector. 4 set screws are used for anchoring the making pyramid system as well as for making angular adjustment for alignment. Apply recommended torque to alignment adjustment screws for connection. Apply loctite to all screws once the alignment and connection is finalized. This product has a 1 year warranty.

P/N	Material	Product Weight	Weight Limit
1265T	Titanium	84g	100kg
1265S	Stainless Steel	131g	100kg



Rotatable Socket Adapter with Pyramid Receiver II

The 4-hole connector receiver is used to connect to any 4-hole thread system and pyramid connection. This adapter can be rotated. Used 4 flat head screws to connect to 4-hole connector. 4 set screws are used for anchoring the making pyramid system as well as for making angular adjustment for alignment. Apply recommended torque to alignment adjustment screws for connection. Apply loctite to all screws once the alignment and connection is finalized. This product has a 1 year warranty.

P/N	Material	Product Weight	Weight Limit
1266A	Aluminium	132g	100kg



4-Ear Connector with Receiver

The 4-ear connector with receiver provides an option for a one step lamination into a transtibial socket. This product has a 2 year warranty.

P/N	Material	Product Weight	Weight Limit
1256T	Titanium	56g	100kg
1256S	Stainless Steel	142g	100kg



4-Prong Rotating Base with Rotating Receiver

The 4-ear connector with rotating receiver provides an option for a one step lamination into a transtibial socket. The 1257T consists of 1223T(4-prong rotating base) and 1216T(rotating receiver). This product has a 2 year warranty.

P/N	Material	Product Weight	Weight Limit
1257T	Titanium	112g	136kg



4-Hole Rotating Base

The 4-hole rotating base provides 360 degrees of rotation for pyramid adapter or pyramid receiver. Used with the 1215T, 1225T/S or 1216T/S. All attachment screws are provided with 4-hole base. The 1214T is manufactured by a forged and machined combination providing for a high quality, light weight and strong product. The product has a 2 year warranty.

P/N	Material	Product Weight	Weight Limit
1214T	Titanium	80g	136kg
1214S	Stainless Steel	120g	125kg