

Tube Clamps



Offset = 5mm (.2in)

1222

OFFSET TUBE CLAMP

The titanium 30mm 1222 tube clamp offers 5mm of offset when extra alignment is needed. It is also ideal when using a pin suspension lock, where prosthetic and pin alignment can be easily adjusted using the offset clamp. This versatile clamp design also provides an offset position that can be rotated 360 degrees.

Warranty: 2 year

| P/N | Material | Product Weight | Weight Limit |
|-------|----------|----------------|----------------|
| 1222T | Titanium | 98g | 136kg / 300lbs |

| Torque Value | Torque (Nm) | Hex (mm) |
|--------------|-------------|------------|
| M6 Cap Screw | 7 Nm | 4mm wrench |
| M8 Set Screw | 15 Nm | 4mm wrench |



1213

10° ANGLED TUBE CLAMP

The 10° titanium 30mm angled adapter is used often with hip disarticulation system. The 10° angle tilt helps at times with alignment associated with hip disarticulation system and as well as transfemoral and transtibial alignment situation.

Warranty: 2 year

| P/N | Material | Product Weight | Weight Limit |
|-------|----------|----------------|----------------|
| 1213T | Titanium | 86g | 100kg / 220lbs |

| Torque Value | Torque (Nm) | Hex (mm) |
|--------------|-------------|------------|
| M5 Cap Screw | 10 Nm | 4mm wrench |
| M8 Set Screw | 15 Nm | 4mm wrench |