FLO-TECH® SOFTIE[™] Protocol

Use in cases where minimizing the effects of injury at bed rest holds a higher priority than early or immediate post-surgical ambulation.

This protocol will help the healing and rehabilitation qualities of the SOFTIE™ and should be applied as early as possible after amputation.

- 1. Attach the OPTIONAL posterior strut (if ordered) at this time.
- 2. Apply a thin, soft dressing as thick as the surgeon deems appropriate for the patient's condition and prognosis.
- 3. *Apply a 2-ply to 3-ply soft amputation sock.
 - a. Gently roll the sock to make application less stressful to the surgical site and less painful to the patient.
 - b. Apply non-allergenic skin glue (Hollister Medical Adhesive [Hollister also makes a solvent for removal]), if desired.
- 4. An optional reticulated pad is available from *FLO-TECH*® and should be applied at this point.
- 5. *Apply an outer 2-ply to 3-ply soft amputation sock to wick away moisture
 - a. Gently roll the sock to make application less stressful to the surgical site and less painful to the patient.
 - b. This sock should be changed 1 to 2 times a day.
- 6. Apply the *FLO-TECH*® SOFTIE™ without the neoprene socket bands to determine the proper interior allowance for the length of the residuum.
 - a. Apply the distal neoprene cap.
 - b. Insert the 1" or 2" distal pad, or both pads (equaling 3") to prevent edema.
 - i. Fill the space between the distal end of the amputated limb and the neoprene cap at the distal portion of the socket.
- 7. Apply the neoprene socket bands snug NOT tight:
 - a. Apply the distal neoprene socket band.
 - b. Apply the neoprene band at the knee area.
 - c. Apply the neoprene thigh band.
 - i. Be sure all exposed tissue is covered.
- 8. Remove the FLO-TECH[®] SOFTIE^{\top} 2 times per day.
 - a. Once in the AM and once in the PM.
 - i. Range the knee per Doctor's orders and instructions from the Physical Therapist.
 - ii. Change outer sock if damp.

*RoyalKnit® CoolMax® socks are available

FLO-TECH® O&P Systems, Inc. PO Box 462 – 7325 Halseyville Road Trumansburg, NY 14886 www.1800flo-tech.com

Phone: (607) 391-1070 Fax: (607) 391-1176 Email: info@1800flo-tech.com

Phone: 1-800-FLO-TECH (356-8324)