## FLO-TECH® SOFTIE<sup>™</sup>-TF Protocol

Use in cases where minimizing the effects of injury at bed rest holds a higher priority than early or immediate post-surgical ambulation.

This protocol will help the healing and rehabilitation qualities of the SOFTIE™-TF and should be applied as early as possible after amputation.

- 1. Apply a thin soft dressing as thick as the Surgeon deems appropriate for the patient's condition and prognosis.
- 2. \*Apply a 2-ply to 3-ply soft amputation sock.
  - a. Gently roll the sock to make application less stressful to the surgical site and less painful to the patient.
  - b. Apply non allergenic skin glue (Hollister Medical Adhesive [Hollister also makes a solvent for removal]), if desired.
- 3. An optional reticulated pad is available from *FLO-TECH*® and should be applied at this point.
- 4. \*Apply an outer 2-ply to 3-ply soft amputation sock to wick away moisture.
  - a. Gently roll the sock to make application less stressful to the surgical site and less painful to the patient.
  - b. This sock should be changed 1 to 2 times a day.
- 5. Apply the *FLO-TECH*® SOFTIE<sup>™</sup>–TF without the neoprene socket bands to determine the proper interior allowance for the length of the residuum.
  - a. Apply the distal neoprene cap.
  - b. Insert a 1", 2" or both pads (equaling 3") to prevent edema.
    - i. Fill the space between the distal end of the amputated limb and the neoprene cap at the distal portion of the socket.
- 6. Apply the neoprene socket bands snug NOT tight.
  - a. Apply the neoprene socket band.
    - i. Be sure all exposed tissue is covered.
- 7. Remove the *FLO-TECH*<sup>®</sup> SOFTIE<sup>™</sup>–TF 2 times per day.
  - a. Once in the AM and once in the PM.
    - i. Range the hip per Doctor's orders and instructions from the Physical Therapist.
    - ii. Change outer sock if damp.
  - \* FLO-TECH® carries pre-rolled Royal Knit® Cool Max® 2-ply amputation socks.

Phone: 1-800-FLO-TECH (356-8324)

Phone: (607) 391-1070

Email: info@1800flo-tech.com

Fax: (607) 391-1176

All materials © FLO-TECH® May 2019