

ALL-TERRAIN KNEE

with optional Stance Flexion



SIMPLIFIED STABILITY

A simple twist-knob engages the manual lock mode, providing additional safety in early rehabilitation or situational use.



PURELY MECHANICAL

The Variable Cadence Controller facilitates multiple walking speeds without the use of hydraulics or pneumatics.



STABLE & EFFICIENT

AutoLock Technology promotes proper gait mechanics that result in a more natural, energy efficient stride.



2-YEAR GUARANTEE

24-month limited manufacturer's warranty



ALL-TERRAIN KNEE

ORIGINAL SERIES

FEATURES & BENEFITS

- Stability provided via the patented AutoLock Technology which engages at full swing phase extension
- Encourages K2 amputees to transition to the K3 mobility level via the patent-pending Variable Cadence Controller
- Increased safety on uneven terrain when simple twist-knob manual lock is engaged
- Durable and weight rated to 275 lb (125 kg)
- Waterproof in fresh water (eg. shower, lake)



INDICATED USERS

- K2 amputees with potential to progress to K3 mobility
- Underinsured amputees who would benefit from a high-functioning and cost-effective prosthetic knee
- Amputees who would benefit from a knee with inherent stability, including hip disarticulation and bilateral
- Amputees in preparatory phase of prosthetic delivery

SUGGESTED L-CODES

L5611, L5845[†], L5850, L5925 [†]Available on stance flexion models only

WARRANTY

24-Month limited manufacturer's warranty

ALL-TERRAIN KNEE

ATK-PA-01



AMPUTATION LEVEL	Transfemoral, Knee Disarticulation	FLEXION ANGLE	150°
MOBILITY LEVEL	K1-K4	PROXIMAL CONNECTION	Pyramid Adaptor
WEIGHT RATING	275 lb (125 kg)	DISTAL CONNECTION	30 mm Tube Clamp
PRODUCT WEIGHT	2.29 lb (1,040 g)	CLEARANCE	¹⁵ ⁄16 in (24 mm)
PRODUCT HEIGHT	7 % in (186 mm)	FITTED HEIGHT	4 ¹⁵ / ₁₆ in (125 mm)

ALL-TERRAIN KNEE WITH STANCE FLEXION

ATK-SF-01



AMPUTATION LEVEL	Transfemoral	FLEXION ANGLE	150°
MOBILITY LEVEL	K1-K4	PROXIMAL CONNECTION	Pyramid Adaptor
WEIGHT RATING	275 lb (125 kg)	DISTAL CONNECTION	30 mm Tube Clamp
PRODUCT WEIGHT	2.71 lb (1,230 g)	CLEARANCE	1 % in (40 mm)
PRODUCT HEIGHT	7 ¹⁵ / ₁₆ in (201 mm)	FITTED HEIGHT	5 % in (141 mm)

^{*}L-Codes suggested by LegWorks are for reference-only, and are subject to change. The responsibility and liability for coding lies with the provider.